

Suitable for tilling in between vineyards and orchards rows with manual side shifting. Four disc groups ensure an optimum soil leveling.



Mounted x-type discharrow is our practical and high maneuverability product that is prefered on narrow spaces. It can be used by small strong tractors, its adjustment and usage are easy. It is used for secondary soil processing, seed-bed preperation, garden agriculture, needless grass, mixing the fertilizer to soil. We have 460mm-510 mm diameter and 20-24-28-32 discs models. Increasing the effect of smashing had been aimed by choosing the disc distance as 175mm. Notched disc alternative can be chosen for hayfields and hard soil conditions. Disc direction angles can be adjusted from the points that the batteries is tied to frame. Working depth can be raised by adding extra weight on to weight section on to the

ATD	Mounted X-Type [	Mounted X-Type Discharrow, Offset				
Model	Number of Disc	Disc Dia (mm)	Working Width (cm)	Weight (kg)	Power* (HP)	
20 ATD 46	20	460	215	400	40 - 50	
24 ATD 46	24	460	230	440	50 - 55	
28 ATD 46	28	460	245	520	55 - 60	
32 ATD 46	32	460	260	600	60 - 70	
20 ATD 51	20	510	215	450	40 - 50	
24 ATD 51	24	510	230	500	50 - 60	
28 ATD 51	28	510	245	590	60 - 70	
32 ATD 51	32	510	260	690	70 - 80	

Disc Spacing is (mm): 175

All Data are not binding and subject to change without prior notice \* Power Requirement may vary depending on soil conditions.





**IDEAL SOIL PREPARATION** 



For Better Farming